

Tapered roller bearing 303-22-XR-JTEKT - 303-22-XR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/303-22-xr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
22	56	17.25	16	13	36.3	36.6	7 700	10 000	303/22XR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	15.7	30.5	31	47.5	44	52	3	4	1.5	1.5	0.59	1.02	0.56	0.210

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952400440
Inside diameter	22 mm
Outside diameter	56 mm
Thickness	17.25 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE