

Tapered roller bearing 30308-XR-JTEKT - 30308-XR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30308-xr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
40	90	25.25	23	20	2	1.5	87.3	98.5	4 600	6 100	30308XR

Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.	r ₁ min.	r ₂ max.	Y ₁	Y ₀				
—	23.8	50	53	80	72	84	3	5	2	1.5	0.55	1.10	0.60	0.780	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952404912
Inside diameter	40 mm
Outside diameter	90 mm
Thickness	25.25 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE