

Tapered roller bearing T2ED050-JTEKT - T2ED050-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/t2ed050-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
50	100	36	35	30	157	196	4 100	5 400	T2ED050					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2ED	24.5	62	58	88	84	94	6	6	2	2	0.34	1.75	0.96	1.28

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250067303
Inside diameter	50 mm
Outside diameter	100 mm
Thickness	36 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE