

Tapered roller bearing T2EE060-JTEKT - T2EE060-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/t2ee060-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
60	115	40	39	33	183	242	3 400	4 600	T2EE060					
Dimension series to ISO355 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2EE	27.6	72	70	103	98	109	6	7	2	2	0.33	1.80	0.99	1.80

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952406022
Inside diameter	60 mm
Outside diameter	115 mm
Thickness	40 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE