

# Tapered roller bearing 33218-JR-JTEKT - 33218-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/33218-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
90	160	55	55	42	343	527	2 400	3 200	33218JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.		r <sub>3a</sub> min.	r <sub>3a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
3FE	40.8	102	101	150	135	154	9	13	2	2	0.42	1.43	0.78	4.76

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409641
Inside diameter	90 mm
Outside diameter	160 mm
Thickness	55 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE