

Tapered roller bearing 30318-R-JTEKT - 30318-R-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30318-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
90	190	46.5	43	36	336	407	2 100	2 700	30318R					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{3a} min.	r _{3a} max.		Y ₁	Y ₀		
—	37.2	108	113	176	165	177	5	10.5	3	2.5	0.35	1.73	0.95	5.78

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122347
Inside diameter	90 mm
Outside diameter	190 mm
Thickness	46.5 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE