

## Tapered roller bearing 33119-JR-JTEKT - 33119-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/33119-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
95	160	49	49	38	304	473	2 300	3 100	33119JR					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>3a</sub> min.	r <sub>3a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
3EE	37.3	107	106	150	138	154	8	11	2	2	0.39	1.54	0.85	3.89

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952409740
Inside diameter	95 mm
Outside diameter	160 mm
Thickness	49 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE