

Tapered roller bearing 30319-DJR-JTEKT - 30319-DJR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30319-djr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
95	200	49.5	45	32	319	391	1 700	2 300	30319DJR					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
7GB	62.7	113	113	186	157	187	6	17.5	3	2.5	0.83	0.73	0.40	6.68

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122378
Inside diameter	95 mm
Outside diameter	200 mm
Thickness	49.5 mm
Packaging	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE