

## Tapered roller bearing 32319-JR-JTEKT - 32319-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32319-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
95	200	71.5	67	55	4	3	517	695	2 000	2 600	<b>32319JR</b>			
Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
260	49.8	113	115	186	166	186	5	16.5	3	2.5	0.35	1.74	0.96	10.1

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125270
Inside diameter	95 mm
Inside diameter	3.74" inch
Outside diameter	200 mm
Outside diameter	7.874" inch
Thickness	71.5 mm
Thickness	2.815" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE