

Tapered roller bearing T2EE100-JTEKT - T2EE100-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/t2ee100-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾	
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.
100	165	47	46	39	3	3	2 200	3 000	T2EE100

Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
2EE	35.1	114	112	151	145	157	7	8	2.5	2.5	0.32	1.88	1.04	3.86

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952410524
Inside diameter	100 mm
Outside diameter	165 mm
Thickness	47 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE