

Tapered roller bearing 33220-JR-JTEKT - 33220-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/33220-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
100	180	63	63	48	3	2.5	431	680	2 100	2 800	33220JR			
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.	r ₃ max.	r ₄ max.		Y ₁	Y ₀		
3FE	45.7	114	112	168	151	172	10	15	2.5	2	0.40	1.48	0.82	6.92

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126727
Inside diameter	100 mm
Outside diameter	180 mm
Thickness	63 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE