

Tapered roller bearing 30320-D-JTEKT - 30320-D-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30320-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
100	215	51.5	47	34	318	374	1 500	2 100			30320D

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	65.9	118	121	201	183	204	5	17	3	2.5	0.81	0.74	0.41	8.02

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122415
Inside diameter	100 mm
Outside diameter	215 mm
Thickness	51.5 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE