

# Tapered roller bearing 31320-JR-JTEKT - 31320-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/31320-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>	
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.			
100	215	56.5	51	35	4	3	373	459	1 500	2 200	<b>31320JR</b>

  

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
7GB	67.7	118	120	201	183	202	6	17.5	3	2.5	0.83	0.73	0.40	8.72

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122828
Inside diameter	100 mm
Inside diameter	3.937" inch
Outside diameter	215 mm
Outside diameter	8.465" inch
Thickness	56.5 mm
Thickness	2.224" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE