

Tapered roller bearing 32221-JR-JTEKT - 32221-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32221-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo

Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No.
d	D	T	B	C	C_r	C_{10}	C_{90}	C_{50}	Grease lub.	Oil lub.	
105	190	53	50	43	3	2.5	392	567	2 000	2 700	32221JR

Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d_a min.	d_a max.	D_a min.	D_a max.	S_a min.	S_a max.	r_a min.	r_a max.	r_b max.	r_b min.		Y_1	Y_0	
3FC	44.8	119	120	178	181	180	6	10	2.5	2	0.42	1.43	0.79	6.37	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250124716
Inside diameter	105 mm
Outside diameter	190 mm
Thickness	53 mm
Weight	6030 g
Packaging	1
Standard	No standard

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE