

# Tapered roller bearing 30321-D-JTEKT - 30321-D-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30321-d-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
105	225	53.5	49	36	4	3	339	396	1 400	2 000	30321D			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	69.1	123	127	211	193	209	6	17	3	2.5	0.81	0.74	0.41	8.76

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122439
Inside diameter	105 mm
Outside diameter	225 mm
Thickness	53.5 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE