

Tapered roller bearing 30321-JTEKT - 30321-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30321-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
105	225	53.5	49	41	4	3	371	432	1 700	2 300	30321

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
—	43.1	123	132	211	193	209	7	12.5	3	2.5	0.35	1.73	0.95	8.74	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250122422
Inside diameter	105 mm
Outside diameter	225 mm
Thickness	53.5 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE