

Tapered roller bearing 32321-JTEKT - 32321-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32321-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
105	225	81.5	77	63	543	707	1 800	2 300			32321

Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	Y ₁	Y ₀				
—	55.7	123	128	211	185	209	8	18.5	3	2.5	0.35	1.73	0.95	13.9	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125300
Inside diameter	105 mm
Outside diameter	225 mm
Thickness	81.5 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE