

Tapered roller bearing 32321-JR-JTEKT - 32321-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32321-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C _{0e}	Grease lub.	Oil lub.		
105	225	81.5	77	63	635	866		1 800	2 300	32321JR	

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
260	56.1	123	128	211	185	209	8	18.5	3	2.5	0.35	1.74	0.96	14.9

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411217
Inside diameter	105 mm
Inside diameter	4.134" inch
Outside diameter	225 mm
Outside diameter	8.858" inch
Thickness	81.5 mm
Thickness	3.209" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE