

## Tapered roller bearing 33022-JR-JTEKT - 33022-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/33022-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
110	170	47	47	37	287	502	2 100	2 800	<b>33022JR</b>					
Dimension series to ISO 955 (Refer.)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer.) Mass (kg)			
		d <sub>1a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> max.	D <sub>2a</sub> min.	S <sub>1a</sub> min.	S <sub>2a</sub> min.		r <sub>3a</sub> max.	r <sub>4a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
20E	33.4	122	123	160	152	161	7	10	2	2	0.29	2.09	1.15	3.81

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126055
Inside diameter	110 mm
Inside diameter	4.331" inch
Outside diameter	170 mm
Outside diameter	6.693" inch
Thickness	47 mm
Thickness	1.85" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE