

# Tapered roller bearing 32222-JR-JTEKT - 32222-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32222-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
110	200	56	53	46	3	2.5	438	640	1 900	2 500	<b>32222JR</b>			
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>3</sub> max.	r <sub>4</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
3FG	46.7	124	126	188	170	190	6	10	2.5	2	0.42	1.43	0.79	7.45

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250124730
Inside diameter	110 mm
Outside diameter	200 mm
Thickness	56 mm
Weight	7154 g
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE