

Tapered roller bearing 31322-JR-JTEKT - 31322-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/31322-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
110	240	63	57	38	452	563	1 400	1 900	31322JR					
Dimension series to ISO995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
7GB	76.2	128	135	226	205	224	6	21	3	2.5	0.83	0.73	0.40	12.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411316
Inside diameter	110 mm
Outside diameter	240 mm
Thickness	63 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE