

Tapered roller bearing 33024-JR-JTEKT - 33024-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/33024-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾						
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.					
120	180	48	48	38	299	540	2 000	2 600	33024JR					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{2a} max.	D _{1a} max.	D _{2a} min.	S _{1a} min.	S _{2a} min.		r _{3a} max.	r _{4a} max.		Y ₁	Y ₀	
2DE	36.2	132	132	170	160	171	6	10	2	2	0.31	1.97	1.08	4.16

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250126079
Inside diameter	120 mm
Outside diameter	180 mm
Thickness	48 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE