

## Tapered roller bearing 30324-JR-JTEKT - 30324-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30324-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
120	260	59.5	55	46	569	714	1 500	2 000	30324JR					
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>3a</sub> min.	r <sub>3a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2GB	50.2	138	152	246	221	239	10	13.5	3	2.5	0.35	1.74	0.96	14.5

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952411439
Inside diameter	120 mm
Outside diameter	260 mm
Thickness	59.5 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE