

Tapered roller bearing 32324-R-JTEKT - 32324-R-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32324-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
120	260	90.5	86	69	4	3	797	1110	1 500	2 000	32324R

Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d ₁ min.	d ₁ max.	d ₂ min.	d ₂ max.	S ₁ min.	S ₁ max.	S ₂ min.	S ₂ max.	r ₁ min.	r ₁ max.		Y ₁	Y ₀	
—	61.1	138	148	246	213	239	9	21.5	3	2.5	0.35	1.73	0.95	21.8	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125362
Inside diameter	120 mm
Outside diameter	260 mm
Thickness	90.5 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE