

Tapered roller bearing 32956-JR-JTEKT - 32956-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32956-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
280	380	63.5	63.5	48	3	2.5	780	1630	770	1000	32956JR			
Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4EC	75.1	294	298	368	347	368	11	15.5	2.5	2	0.43	1.39	0.76	20.14

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125812
Inside diameter	280 mm
Inside diameter	11.024" inch
Outside diameter	380 mm
Outside diameter	14.961" inch
Thickness	63.5 mm
Thickness	2 1/2" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE