

Tapered roller bearing 32056-JR-JTEKT - 32056-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32056-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
280	420	87	87	65	1 200	2 280	720	960	32056JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4FC	91.1	302	305	402	370	402	14	22	4	3	0.46	1.31	0.72	41.7

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123832
Inside diameter	280 mm
Outside diameter	420 mm
Thickness	87 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE