

Tapered roller bearing 30260-JTEKT - 30260-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30260-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
300	540	96	85	71	1510	2360	550	730			30260

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	103.9	328	350	518	475	505	14	24	5	4	0.42	1.44	0.79	84.7

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412078
Inside diameter	300 mm
Inside diameter	11.811" inch
Outside diameter	540 mm
Outside diameter	21.26" inch
Thickness	96 mm
Thickness	3.78" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE