

Tapered roller bearing 32064-JR-JTEKT - 32064-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32064-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--------------------------------------|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 320 | 480 | 100 | 100 | 74 | 1510 | 2810 | 600 | 800 | 32064JR | | | | | |
| Dimension series to ISO95 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S ₁ min. | S ₂ min. | r ₃ min. | r ₄ max. | | Y ₁ | Y ₀ | | |
| 4GD | 103.0 | 342 | 344 | 462 | 418 | 461 | 16 | 26 | 4 | 3 | 0.46 | 1.31 | 0.72 | 58.7 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250306822 |
| Inside diameter | 320 mm |
| Outside diameter | 480 mm |
| Thickness | 100 mm |
| Weight | 58700 g |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE