

## Tapered roller bearing 30264-JTEKT - 30264-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30264-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
320	580	104	92	75	8	5	1740	2770	490	660	30264

  

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
—	111.9	348	370	558	505	540	14	28	5	4	0.42	1.44	0.79	108	

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952412108
Inside diameter	320 mm
Inside diameter	12.598" inch
Outside diameter	580 mm
Outside diameter	22.835" inch
Thickness	104 mm
Thickness	4.094" inch
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE