

Tapered roller bearing 32026-JR-JTEKT - 32026-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32026-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | | | | |
| 130 | 200 | 45 | 45 | 34 | 340 | 563 | | | 1 800 | 2 300 | 32026JR | | | |
| Dimension series to ISO 995 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | | |
| 4EC | 42.9 | 142 | 144 | 190 | 178 | 192 | 8 | 11 | 2 | 2 | 0.43 | 1.38 | 0.76 | 5.04 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250123603 |
| Inside diameter | 130 mm |
| Outside diameter | 200 mm |
| Thickness | 45 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE