

Tapered roller bearing 30230-JR-JTEKT - 30230-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30230-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | | | |
|-------------------------------------|--------------------|--------------------------|----------------------|-------------------------|----------------------|--------------------------------------|----------------------|---------------------------|----------------------|------------|-----------------------------------|-----------------------------------|--------------------|------|
| d | D | T | B | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | | |
| 150 | 270 | 49 | 45 | 38 | 483 | 664 | 1 300 | 1 800 | 30230JR | | | | | |
| Dimension series to ISO995 (Refer.) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | | | |
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | Constant e | Axial load factors Y ₁ | Axial load factors Y ₀ | (Refer.) Mass (kg) | |
| 4GB | 52.4 | 168 | 175 | 256 | 234 | 255 | 9 | 11 | 3 | 2.5 | 0.44 | 1.38 | 0.76 | 11.6 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 4549250258749 |
| Inside diameter | 150 mm |
| Inside diameter | 5.906" inch |
| Outside diameter | 270 mm |
| Outside diameter | 10.63" inch |
| Thickness | 49 mm |
| Thickness | 1.929" inch |
| Weight | 10500 g |
| Packaging | 1 |
| Standard | No standard |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE