

Tapered roller bearing 32230-JR-JTEKT - 32230-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32230-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾						
d	D	T	B	C	C _r	C _{0r}	Grease lub.		Oil lub.					
150	270	77	73	60	704	1070	1300	1800	32230JR					
Dimension series to ISO 995 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.		r _{1a} min.	r _{1a} max.		Y ₁	Y ₀	
4GD	65.2	168	170	256	226	254	8	17	3	2.5	0.44	1.38	0.76	18.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250240935
Inside diameter	150 mm
Outside diameter	270 mm
Thickness	77 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE