

Tapered roller bearing 32330-R-JTEKT - 32330-R-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32330-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.				
150	320	114	108	90	5	4	1240	1790	1200	1600	32330R			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	78.4	172	187	302	263	298	10	17	4	3	0.35	1.74	0.96	42.0

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250233319
Inside diameter	150 mm
Outside diameter	320 mm
Thickness	114 mm
Weight	42000 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE