

Tapered roller bearing 32032-JR-JTEKT - 32032-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32032-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | | | | |
| 160 | 240 | 51 | 51 | 38 | 3 | 2.5 | 440 | 758 | 1 400 | 1 900 | 32032JR | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d _{1a} min. | d _{1a} max. | D _{2a} min. | D _{2a} max. | S _{1a} min. | S _{1a} max. | r _{3a} min. | r _{3a} max. | | Y ₁ | Y ₀ | | |
| 4EC | 52.1 | 174 | 175 | 228 | 213 | 231 | 8 | 13 | 2.5 | 2 | 0.46 | 1.31 | 0.72 | 7.75 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952421230 |
| Inside diameter | 160 mm |
| Outside diameter | 240 mm |
| Thickness | 51 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE