

## Tapered roller bearing 30234-JR-JTEKT - 30234-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30234-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0e</sub>	C <sub>0i</sub>	Grease lub.	Oil lub.	
170	310	57	52	43	620	867			1 100	1 500	30234JR

  

Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4GB	61.2	192	202	292	269	288	8	14	4	3	0.44	1.38	0.76	17.8

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421315
Inside diameter	170 mm
Inside diameter	6.693" inch
Outside diameter	310 mm
Outside diameter	12.205" inch
Thickness	57 mm
Thickness	2.244" inch
Weight	17800 g
Packaging	1
Standard	No standard

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE