

Tapered roller bearing 30334-JR-JTEKT - 30334-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30334-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.							
170	360	80	72	62	1040	1370	1000	1300	30334JR						
Dimension series to ISO355 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer.1) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{1b} min.	r _{1b} max.		Y ₁	Y ₀	
2GB	67.9	192	218	342	306	329	13	18	4	3	0.35	1.74	0.96	37.5	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421346
Inside diameter	170 mm
Outside diameter	360 mm
Thickness	80 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE