

Tapered roller bearing 30338-D-JTEKT - 30338-D-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30338-d-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾						
d	D	T	B	C _r	C _{0r}	Grease lub.	Oil lub.							
190	400	86	78	52	90	1210	740	1000	30338D					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer.) Mass (kg)	
—	119.2	218	232	378	350	372	11	34	5	4	0.81	0.74	0.41	44.8

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421544
Inside diameter	190 mm
Outside diameter	400 mm
Thickness	86 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE