

Tapered roller bearing 32340-JTEKT - 32340-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32340-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾	
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.			
200	420	146	138	115	6	5	1 790	2 580	830	1 100	32340

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	d _{2a} min.	d _{2a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	102.9	228	240	398	345	395	16	30	5	4	0.35	1.73	0.95	91.0

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421636
Inside diameter	200 mm
Inside diameter	7.874" inch
Outside diameter	420 mm
Outside diameter	16.535" inch
Thickness	146 mm
Thickness	5.748" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE