

## Tapered roller bearing 32944-JR-JTEKT - 32944-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32944-jr-jtekt>

Single-row tapered roller bearings  
metric series

**Koyo**



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
220	300	51	51	39	3	2.5	498	1 010	1 000	1 400	<b>32944JR</b>			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
3EC	58.6	234	234	288	275	290	9	12	2.5	2	0.43	1.41	0.78	10.1

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250125799
Inside diameter	220 mm
Outside diameter	300 mm
Thickness	51 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE