

Tapered roller bearing 32044-JR-JTEKT - 32044-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32044-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
220	340	76	76	57	894	1620	940	1300			32044JR

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
4FD	72.8	238	243	326	300	326	12	19	3	2.5	0.43	1.39	0.77	25.2

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123788
Inside diameter	220 mm
Outside diameter	340 mm
Thickness	76 mm
Packaging	-

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE