

Tapered roller bearing 30244-JR-JTEKT - 30244-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30244-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|----|----|----|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | |
| 220 | 400 | 72 | 65 | 54 | 5 | 4 | 1010 | 1440 | 830 | 1100 | 30244JR |

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) |
|----------------------------------------|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|------------|--------------------|----------------|----------------------|
| | | d _{1a} min. | d _{1a} max. | d _{2a} min. | d _{2a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | | Y ₁ | Y ₀ | |
| — | 76.5 | 242 | 263 | 382 | 344 | 371 | 14 | 17 | 4 | 3 | 0.44 | 1.43 | 0.79 | 35.9 | |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952421674 |
| Inside diameter | 220 mm |
| Inside diameter | 8.661" inch |
| Outside diameter | 400 mm |
| Outside diameter | 15.748" inch |
| Thickness | 72 mm |
| Thickness | 2.835" inch |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE