

Tapered roller bearing 32948-JR-JTEKT - 32948-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32948-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
240	320	51	51	39	3	2.5	515	1090	940	1300	32948JR

Dimension series to ISO 355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer.) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{2a} min.	r _{2a} max.		Y ₁	Y ₀	
4EC	64.5	254	254	308	294	311	9	12	2.5	2	0.46	1.31	0.72	10.9	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421704
Inside diameter	240 mm
Inside diameter	9.449" inch
Outside diameter	320 mm
Outside diameter	12.598" inch
Thickness	51 mm
Thickness	2.008" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE