

Tapered roller bearing 32048-JR-JTEKT - 32048-JR-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/32048-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.					
240	360	76	76	57	924	1720			870	1200	32048JR				
Dimension series to ISO355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer.) Mass (kg)
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	r _{2a} min.	r _{2a} max.		Y ₁	Y ₀	
4FD	78.5	258	261	346	318	346	12	19	3	2.5	0.46	1.31	0.72	26.8	

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250123795
Inside diameter	240 mm
Inside diameter	9.449" inch
Outside diameter	360 mm
Outside diameter	14.173" inch
Thickness	76 mm
Thickness	2.992" inch
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE