

Tapered roller bearing 30252-JTEKT - 30252-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/30252-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾			
d	D	T	B	C	C _r	C _{0r}	C _{0r}	C _{0r}	Grease lub.	Oil lub.				
260	480	89	80	67	6	5	1210	1860	650	870	30252			
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
—	93.6	288	310	458	415	450	14	21	5	4	0.42	1.44	0.79	64.9

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952421780
Inside diameter	260 mm
Outside diameter	480 mm
Thickness	89 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE