


Tapered roller bearing 03062-03162-JTEKT - 03062-03162-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/03062-03162-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
15.875	41.275	14.288	14.681	11.112	1.2	2.0	21.8	20.5	11 000	14 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
03062	03162	9.3	21.5	20.0	34.0	37.5	1.2	2.0	0.31	1.93	1.06	0.060	0.035

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425344
Inside diameter	15.875 mm
Inside diameter	5/8" inch
Outside diameter	41.275 mm
Outside diameter	1 5/8" inch
Thickness	14.288 mm
Thickness	9/16" inch
Weight	118 g
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE