

Tapered roller bearing 02473-02420-JTEKT - 02473-02420-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/02473-02420-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|----------------|----------------|----------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | r ₁ | r ₂ | r ₃ | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 25.400 | 68.262 | 22.225 | 22.225 | 17.462 | 0.8 | 1.6 | | 51.0 | 61.1 | 6 000 | 8 000 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer to Mass (kg)) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|----------------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _a max. | r _b max. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 02473 | 02420 | 17.1 | 34.5 | 33.5 | 59.0 | 63.0 | 0.8 | 1.6 | 0.42 | 1.44 | 0.79 | 0.275 | 0.150 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | JTEKT |
| N° Ean13 | 3663952425719 |
| Inside diameter | 25.4 mm |
| Outside diameter | 68.262 mm |
| Thickness | 22.225 mm |
| Packaging | 1 |

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE