

Tapered roller bearing HM88630-HM88610-JTEKT - HM88630-HM88610-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/hm88630-hm88610-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)								Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_1 max.	r_2 max.	C_r	C_{10}	Grease lub.	Oil lub.	
25.400	72.233	25.400	25.400	19.842	0.8	2.4	86.9	87.4	5 700	7 600	

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	a	d_a	d_b	D_a	D_b	r_a max.	r_b max.	e	Y_1	Y_2	Inner ring	Outer ring
HM88630	HM88610	20.7	39.5	39.5	60.0	69.0	0.8	2.4	0.55	1.10	0.60	0.391	0.185

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425733
Inside diameter	25.4 mm
Outside diameter	72.233 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE