

## Tapered roller bearing 2688-2631-JTEKT - 2688-2631-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/2688-2631-jtekt>

Single-row tapered roller bearings inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r_1$ max.	$r_2$ max.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
26.988	66.421	23.812	25.433	19.050	1.6	1.2	67.0	75.2	6 500	8 700

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
2688	2631	13.9	35.0	33.0	58.0	60.0	1.6	1.2	0.25	2.36	1.30	0.262	0.163

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425832
Inside diameter	26.988 mm
Outside diameter	66.421 mm
Thickness	23.812 mm
Packaging	1

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE