


Tapered roller bearing 15112-15245-JTEKT - 15112-15245-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/15112-15245-jtekt>

Single-row tapered roller bearings inch series **Koyo**



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i>	<i>r_b</i>	<i>C_r</i>	<i>C_{0r}</i>	Grease lub.	Oil lub.
28.575	62.000	19.050	20.638	14.288	3.6	1.2	44.6	50.7	6 400	8 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
15112	15245	13.2	40.0	34.0	55.0	58.0	3.6	1.2	0.35	1.71	0.94	0.193	0.081

PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952425856
Inside diameter	28.575 mm
Outside diameter	62 mm
Thickness	19.05 mm
Packaging	1

contact@123bearing.com

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE