


## Tapered roller bearing 26112-26283-JTEKT - 26112-26283-JTEKT

<https://www.123bearing.com/bearing-housing/roller-bearing/tapered/26112-26283-jtekt>

Single-row tapered roller bearings ————— **Koyo**  
inch series



| Boundary dimensions (mm) |          |          |          |          |                               |                               | Basic load ratings (kN) |                        | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> <sub>a</sub><br>max. | <i>r</i> <sub>b</sub><br>max. | <i>C</i> <sub>r</sub>   | <i>C</i> <sub>10</sub> | Grease lub.                          | Oil lub. |
| 28.575                   | 72.000   | 19.000   | 18.900   | 15.875   | 1.6                           | 1.6                           | 47.5                    | 49.6                   | 5 900                                | 7 800    |

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                       |                       |                       |                               |                               | Con-stant | Axial load factors    |                       | (Refer) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|-----------|-----------------------|-----------------------|-------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d</i> <sub>a</sub>    | <i>d</i> <sub>b</sub> | <i>D</i> <sub>a</sub> | <i>D</i> <sub>b</sub> | <i>r</i> <sub>a</sub><br>max. | <i>r</i> <sub>b</sub><br>max. | <i>e</i>  | <i>Y</i> <sub>1</sub> | <i>Y</i> <sub>2</sub> | Inner ring        | Outer ring |
| 26112       | 26283      | 15.3             | 37.0                     | 35.0                  | 62.0                  | 65.0                  | 1.6                           | 1.6                           | 0.36      | 1.67                  | 0.92                  | 0.217             | 0.163      |

### PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 3663952425887 |
| Inside diameter  | 28.575 mm     |
| Inside diameter  | 1 1/8" inch   |
| Outside diameter | 72 mm         |
| Outside diameter | 2.835" inch   |
| Thickness        | 19 mm         |
| Thickness        | 0.748" inch   |
| Packaging        | 1             |

[contact@123bearing.com](mailto:contact@123bearing.com)

(646) 712 9672

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE